## NORTH EAST COLOR



## Vinyl Decal - Window 2nd Surface

## **INSTALLATION GUIDE**

ver. 070623

For Support Call: 603.436.8210

## **Vinyl Decal Installation**

Please note this decal mounts to the inside surface of the window and is viewed from the outside.

Begin by cleaning the mounting surface of any dust, fingerprints or smudges with a clean rag and isopropyl alcohol. Allow the surface to dry thoroughly.

Place the decal in the general location by using a tab of masking tape on each side of the decal. Now you can adjust placement using a measuring tape to ensure proper height and spacing of your choosing. A small level can be used to insure that the graphic and text are level.

Once decal is in desired location run a piece of masking tape down the middle of the decal. Make sure there is enough excess tape on both sides to insure the decal remains anchored in place on the mounting surface. Carefully pull one side of the decal up away from the backing liner at a 45 degree angle. Using a utility knife cut away the excess liner.

• Hold the exposed decal just over the mounting surface making sure that it is taut. Start applying the decal from the center using the squeegee with firm overlapping strokes. The squeegee should be held at a 45 degree angle to prevent trapped air bubbles.

S Now that half of the decal has been applied and it is fully anchored to the surface- you can now remove the remaining masking tape. Peel back the other half of the decal, remove the remaining backing liner, and apply the rest of the decal in the same manner.